



Torque shut-off screwdriver with ParameterControl Baton offset screwdriver, Type: 71126360



Order data

| | |
|--------------|-----------------|
| Order number | 071120 71126360 |
| GTIN | 4014586883847 |
| Item class | 03F |

Description

Version:

FEIN ACCU TEC shut-off screwdrivers are designed for the most demanding applications requiring **precise screw tightening in series production**.

- **Brushless EC motors with working life extended by a factor of several times and up to 80 % lower maintenance costs.**
- **Restart delay after the screw tightening, to avoid "follow-up".**
- **Restart inhibit if the remaining battery charge is insufficient to perform the screw tightening.**
- **Tight screw tightening tolerances for high screw tightening quality.**
- **Precise and consistent tightening torques in any screw tightening application.**
- **Testable screwdrivers, CmK-value > 1.67 ±10% (based on 6 sigma) to ISO 5393 VDI/VDE 2647.**

The release torque is 25 % above the tightening torque.

Torque shut-off screwdriver with ParameterControl for easy and individual programming on a PC, using the programming adaptor (No. 071135 size 92604163).

Freely programmable parameters: Speed, direction of rotation, angle of rotation, torque threshold and time.

Up to 5 programmable steps. Precise configuration for each screw tightening application. **Final switch-off by mechanical clutch.** Ideal for optimising the process and time.

Shut-off screwdriver, takes a Li-ion battery. Maintenance-free up to 500,000 screw fastenings.

Supplied with:

Just the screwdriver itself is supplied, **without battery, charger or setting tool and angle head**. Please order the battery, charger, setting tool and angle head specifically for the device.

Note:

See No. 073832 ff. for suitable rechargeable batteries and chargers.

See No. 654300 ff. for torque analysers.

See No. 654381 for torque sensors / rotational angle sensors.

Calibration service on request.

suitable battery - supplier / battery type / voltage: Fein type E 12 V

suitable battery - supplier / battery type / voltage: Fein type E 18 V

Manufacturer's designation: ASW 18-45 PC

Battery voltage: 12 V

Battery voltage: 18 V

Torque range: 20 - 45 N·m

Speed range: 25 - 310 min⁻¹

Format: Baton offset screwdriver

Technical description

| | |
|--|------------------------------|
| Motor design | Brushless EC motor |
| Manufacturer's designation | ASW 18-45 PC |
| Speed range | 25 - 310 min ⁻¹ |
| Weight including rechargeable battery | 1.7 kg |
| Format | Baton offset screwdriver |
| Battery voltage | 12 V |
| Battery voltage | 18 V |
| Torque range | 20 - 45 N·m |
| suitable angle head | 071133 15010 |
| suitable battery - supplier / battery type / voltage | Fein type E 12 V |
| suitable battery - supplier / battery type / voltage | Fein type E 18 V |
| Type of rechargeable battery | Lithium-ion |
| Power supply | Rechargeable battery-powered |
| Type of product | Screwdriver |

Accessories

| | |
|--|-----------------|
| Li-ion battery Battery type, battery voltage FE18 V | 073838 FE18 |
| Angle head for ASW 18 Type 26020 | 071133 26020 |
| Battery charger Type FE80 | 073845 FE80 |
| Programming adaptor Type 92604163 | 071135 92604163 |
| Li-ion battery Rechargeable battery type, battery voltage FE18 V | 073835 FE18 |
| ACCU TEC setting tool Type ESTW | 071119 ESTW |
| Electronic torque tool tester "TTT" | 654340 |
| Battery charger Type FE30 | 073845 FE30 |
| Battery charger Type FE50 | 073845 FE50 |