

All-plastic cable drum for F, B, PL and CZ, Type: 25B2



Order data

| Order number | 081134 25B2 |
|--------------|---------------|
| GTIN | 4003644022526 |
| Item class | 08B |

Description

Version:

Hedi® cable drums stand for "Made in Germany" quality and a long service life. The drum body is specially designed to optimally guide the cable. The integrated rotation stop switch prevents accidental drum rotation. All cable drums are equipped with thermal cut-out switches.

Sturdy cable drum of high-impact plastic with **thermal overload protection**.

- · 400 V CEE input plug 16 A.
- 400 V CEE output plug 16 A with spring-loaded cover.
- Two 250 V standard Schuko sockets with spring-loaded covers.
- · Conductor cross-section 2.5 mm.

Certified for continuous exterior use and for use in humid environments.

With 250 V sockets for F, B, PL, and CZ.

Function:

IP44: Protected against splashed water from all directions and protected against penetration by foreign bodies with $\emptyset > 1$ mm, however tools and wires should be kept away.

IP Index of Protection: IP 44

impact-resistant and splash-proof: Category 2 (K2) to BGI

Rated power unrolled: 5500 (16 A) W

Cable class: H07BQ-F
Cable structure: 5G2.5

Material cable: Armoured cable

Cable length: 25 m

Technical description

| Material cable | Armoured cable |
|-----------------------------------|------------------------|
| Material of body | All-plastic |
| Rated power unrolled | 5500 (16 A) W |
| Cable structure | 5G2.5 |
| Cable class | H07BQ-F |
| Cable length | 25 m |
| impact-resistant and splash-proof | Category 2 (K2) to BGI |
| IP Index of Protection | IP 44 |
| Nominal voltage | 400 V |
| Power supply | Mains operated |
| Type of product | Cable drum |