

mato

Lube-Shuttle® pneumatic grease gun, 400 g



Order data

Order number	083587
GTIN	4016553037307
Item class	08H

Description

Version:

One-handed pneumatic grease guns, outstandingly well balanced. **Single-shot system for optimum grease management (1 cm³ / stroke)**, pressure ratio 1:60.

Refilling with Lube-Shuttle® cartridges (contents: 400 g).

Suitable for greases up to NLGI class 3 and very low temperatures.

Supplied with:

Rubberised armoured hose, 4-jaw hydraulic push-on connector.

Working pressure: 400 bar

Test pressure: 800 bar

Hose connection thread: R1/8 in

Operational range compressed air supply: 3 - 8 bar

Technical description

Working pressure	400 bar
Test pressure	800 bar
Hose connection thread	R1/8 in
Operational range compressed air supply	3 - 8 bar
Product name attribute	400 g

Type of product

Grease gun

Accessories

4-jaw hydraulic push-on connector Connection thread 1/8

083589 1/8

Nozzle with universal connector Connection thread 1/8

083583 1/8

4-jaw hydraulic push-on connector safeLOCK Connection thread 1/8

083596 1/8

Armoured hose with 4-jaw hydraulic push-on connector Connection thread 1/8

083586 1/8

Armoured hose with push-on connector Connection thread 1/8

083588 1/8

Nozzle with conical connector Connection thread 1/8

083584 1/8