

Garant
Solid carbide jobber drill extra short, TiAlN, Ø DC h7: 0,5mm

Order data

Order number	122151 0,5
GTIN	4045197747969
Item class	11E

Description
Version:

Similar to DIN 6539 (extra short).

Nominal Ø and shank Ø equal.

TiAlN coating for even better performance.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Non slip clamping in drill chuck No. 341050 with diamond coated jaws.

Through-coolant: no

Standard: DIN 6539

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 2.3 mm

Overall length L: 20 mm

Shank Ø D_s : 0.5 mm

Feed f in steel < 1100 N/mm²: 0.01 mm/rev.

Technical description

Nominal Ø D_c	0.5 mm
Overall length L	20 mm
Tolerance nominal Ø	h7
Standard	DIN 6539
Shank tolerance	h7

Feed f in steel < 1100 N/mm ²	0.01 mm/rev.
Number of cutting edges Z	2
Flute length L _c	3 mm
Shank Ø D _s	0.5 mm
recommended maximum drilling depth L ₂	2.3 mm
Coating	TiAlN
Tool material	solid carbide
Type	N
Point angle	118 °
Helix angle	30 °
Shank	Parallel shank to h7
Through-coolant	no
Colour ring	without
Type of product	Jobber drill

User data

	Suitability	V _c	ISO code
Alu plastics	suitable only under restricted conditions	260 m/min	N
Aluminium (short chipping)	suitable	180 m/min	N
Alu > 10% Si	suitable	180 m/min	N
Steel < 500 N/mm ²	suitable	90 m/min	P
Steel < 750 N/mm ²	suitable	90 m/min	P
Steel < 900 N/mm ²	suitable	80 m/min	P
Steel < 1100 N/mm ²	suitable	60 m/min	P
Steel < 1400 N/mm ²	suitable	35 m/min	P
INOX < 900 N/mm ²	suitable	35 m/min	M
INOX > 900 N/mm ²	suitable	25 m/min	M

Ti > 850 N/mm ²	suitable	25 m/min	S
GG(G)	suitable	90 m/min	K
CuZn	suitable	180 m/min	N
Uni	suitable		
Oil	suitable		
wet maximum	suitable		
dry	suitable only under restricted conditions		