

**Garant**
**GARANT Master Alu solid carbide high-performance reamer HPC through hole, DLC, Nominal Ø DC: 4H7mm**

**Order data**

Order number	164400 4H7
GTIN	4062406282042
Item class	10P

**Description**
**Version:**

**Special** HPC reamers of the latest generation, **for machining aluminium**, with improved tooth geometry and further developed carbide substrate. Extra-short teeth for increased cutting performance values. Optimised cooling strategy with radially arranged coolant outlets aligned directly to the teeth. **Version suitable for NC** with straight shank Ø for standard arbors especially in **hydraulic chucks** or **high precision collet chucks**. Very high concentricity and process reliability due to unequal spacing of the teeth and special profile of the round chamfer width.

Version with DLC sp<sup>2</sup> coating.

**Tolerance specifications:**

**Configurable:** Reamers finish ground to match your specification.

**H7:** Version to DIN1420 for H7 bore tolerance.

**Application:**

Special version for through holes.

Tolerance: H7

Number of cutting edges Z: 4

Tolerance: H7

Flute length L<sub>c</sub>: 8 mm

Overhang L<sub>1</sub>: 39 mm

Overall length L: 75 mm

Number of cutting edges Z: 4

Shank Ø D<sub>s</sub>: 6 mm

**Technical description**

Overhang $L_1$	39 mm
Tolerance	H7
Feed $f$ in cast alu	0.6 mm/rev.
Number of cutting edges $Z$	4
Shank $\varnothing D_s$	6 mm
Flute length $L_c$	8 mm
Series	Master Alu
Nominal $\varnothing D_c$	4 mm
Overall length $L$	75 mm
Reaming oversize in diameter	0.1 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Through-coolant	yes, with 25 bar
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for through holes
Colour ring	yellow
Type of product	Phillips bit

## User data

	Suitability	$V_c$	ISO code
Aluminium	suitable	250 m/min	N
Aluminium (short chipping)	suitable	250 m/min	N
Alu > 10% Si	suitable	250 m/min	N
wet maximum	suitable		
wet minimum	suitable		

