

Garant

GARANT Master Alu PickPocket solid carbide roughing end mill with through-coolant HPC, DLC, Ø e8 DC: 16mm



Order data

Order number	202015 16
GTIN	4062406380984
Item class	11X

Description

Version:

For roughing and finishing.

Up to $2 \times D$ into solid material at very high feed rates and smooth cutting action.

Very high feed rates when plunging vertically.

Ramping capability up to 45° .

Improved chip evacuation due to central through-coolant.

With the latest generation of DLC coating sp^2 .

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Note:

A minimum oversize of $0.1 \times D$ must be maintained for subsequent finishing operations.

Tolerance nominal \varnothing : e8

No. of teeth Z: 3

Helix angle: 42°

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 31 mm

Overhang length L_1 incl. recess: 58 mm

Recess $\varnothing D_1$: 15.8 mm

Overall length L: 108 mm

Shank $\varnothing D_s$: 16 mm

Technical description

Feed f_z for slot milling in short-chipping aluminium	0.12 mm
Overhang length L_1 incl. recess	58 mm
No. of teeth Z	3
Direction of infeed	horizontal, oblique and vertical
Feed f_z for side milling in short-chipping aluminium	0.14 mm
Overall length L	108 mm
Flute length L_c	31 mm
Balance quality with shank	G 2.5 with HA
Recess $\varnothing D_1$	15.8 mm
Shank $\varnothing D_s$	16 mm
Corner rounding r_v	0.32 mm
Helix angle	42°
Shank	DIN 6535 HA to h6
Cutting edge $\varnothing D_c$	16 mm
Tolerance nominal \varnothing	e8
Series	Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	yes
Machining strategy	HPC
Colour ring	yellow
Type of product	End / face mill

User data

	Suitability	V _c	ISO code
Aluminium	Suitable	550 m/min	N
Aluminium (short chipping)	suitable	500 m/min	N
Alu > 10% Si	Suitable	450 m/min	N
PMMA acrylic	Suitable	200 m/min	N
PE-HD	Suitable	160 m/min	N
PA 66	Suitable	200 m/min	N
PEEK	Suitable	150 m/min	N
PF 31	Suitable	130 m/min	N
PVDF GF20	Suitable	180 m/min	N
POM GF25	Suitable	160 m/min	N
PA 66 GF30	Suitable	150 m/min	N
PEEK GF30	Suitable	130 m/min	N
PTFE CF25	Suitable	160 m/min	N
Honeycomb sandwich	suitable only under restricted conditions	300 m/min	N
Cu	Suitable	160 m/min	N
CuZn	Suitable	200 m/min	N
wet maximum	Suitable		
Air	Suitable		

Services

Shank grinding Type HB

129100 HB