



HOLEX Pro Steel solid carbide roughing end mill HPC, TiAlN, Ø DC: 8mm



Order data

Order number	203058 8
GTIN	4045197946270
Item class	12X

Description

Version:

For **roughing and finishing**.

Up to $0.7 \times D$ into solid material **at very high feed rates** with smooth cutting action.

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Tolerance nominal \varnothing : 0 / -0.03

No. of teeth Z: 4

Helix angle: 38°

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 24 mm

Overhang length L_1 incl. recess: 30 mm

Recess $\varnothing D_1$: 7.5 mm

Overall length L: 68 mm

Shank $\varnothing D_s$: 8 mm

Technical description

Feed f_z for side milling in steel $< 900 \text{ N/mm}^2$	0.06 mm
Tolerance nominal \varnothing	0 / -0.03
Direction of infeed	horizontal, oblique and vertical
Corner chamfer width at 45°	0.2 mm
Shank $\varnothing D_s$	8 mm

Cutting edge $\varnothing D_c$	8 mm
No. of teeth Z	4
Feed f_z for slot milling in steel < 900 N/mm ²	0.05 mm
Overall length L	68 mm
Overhang length L_1 incl. recess	30 mm
Helix angle	38 °
Flute length L_c	24 mm
Recess $\varnothing D_1$	7.5 mm
Shank	DIN 6535 HB to h6
Corner chamfer angle	45 °
Series	Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.25×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End / face mill

User data

	Suitability	V_c	ISO code
Steel < 500 N/mm ²	suitable	260 m/min	P
Steel < 750 N/mm ²	suitable	240 m/min	P
Steel < 900 N/mm ²	suitable	180 m/min	P

Steel < 1100 N/mm ²	suitable	160 m/min	P
INOX < 900 N/mm ²	suitable only under restricted conditions	80 m/min	M
GG(G)	suitable	250 m/min	K
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	suitable		
Air	suitable		