

Garant

GARANT Master UNI solid carbide roughing end mill HPC, TiSiN, Ø e8 DC: 3mm



Order data

Order number	203067 3
GTIN	4062406569617
Item class	11Z

Description

Version:

For **roughing and finishing at very high feed rates** with smooth cutting action. **Newly developed geometry and high-performance coating** for outstanding production results and very long tool life with a variety of materials. Unequal spacing gives **high intrinsic stability** and smooth cutting action.

Advantage:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 42 °

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 8 mm

Overhang length L_1 incl. recess: 13 mm

Recess Ø D_1 : 2.8 mm

Overall length L: 57 mm

Shank Ø D_s : 6 mm

Technical description

Flute length L_c	8 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.025 mm
Direction of infeed	horizontal, oblique and vertical

Helix angle	42°
Feed f_z for side milling in INOX > 900 N/mm ²	0.015 mm
Overall length L	57 mm
Feed f_z for slot milling in stainless steel > 900 N/mm ²	0.012 mm
Shank $\varnothing D_s$	6 mm
Overhang length L_1 incl. recess	13 mm
No. of teeth Z	4
Tolerance nominal \varnothing	e8
Cutting edge $\varnothing D_c$	3 mm
Shank	DIN 6535 HB to h6
Recess $\varnothing D_1$	2.8 mm
Feed f_z for slot milling in steel < 900 N/mm ²	0.02 mm
Corner rounding r_v	0.06 mm
Coating	TiSiN
Tool material	solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	green
Type of product	End / face mill

User data

	Suitability	V_c	ISO code
--	-------------	-------	----------

Aluminium (short chipping)	suitable only under restricted conditions	280 m/min	N
Steel < 500 N/mm ²	suitable	260 m/min	P
Steel < 750 N/mm ²	suitable	240 m/min	P
Steel < 900 N/mm ²	suitable	190 m/min	P
Steel < 1100 N/mm ²	suitable	180 m/min	P
Steel < 1400 N/mm ²	suitable	150 m/min	P
INOX < 900 N/mm ²	suitable	90 m/min	M
INOX > 900 N/mm ²	suitable	80 m/min	M
Ti > 850 N/mm ²	suitable only under restricted conditions	40 m/min	S
GG(G)	suitable	250 m/min	K
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	suitable		
Air	suitable		