



Solid carbide milling cutter with chip separators TPC, TiAlN, Ø f8 DC: 10mm



Order data

Order number	203095 10
GTIN	4062406117351
Item class	12X

Description

Version:

High-performance milling cutter specially designed for general-purpose TPC applications. Strengthened core.

Optimised bending strength due to the use of ultra-fine grain substrates.

Chip separator for controlled chip breaking.

Note:

h_{max} : The values stated in the table are maximum values.

$a_{e,max} = 0.07 \times D$ for TPC machining.

Tolerance nominal Ø: f8

No. of teeth Z: 5

Helix angle: 40 °

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 5

Flute length L_c : 30 mm

Overhang length L_1 incl. recess: 35 mm

Recess Ø D_1 : 9.8 mm

Overall length L: 80 mm

Shank Ø D_s : 10 mm

Technical description

Average chip thickness h_{max} for TPC milling in Toolox 44 HRC	0.051 mm
Direction of infeed	horizontal and oblique

Flute length L_c	30 mm
Helix angle	40 °
Recess $\varnothing D_1$	9.8 mm
No. of teeth Z	5
Overhang length L_1 incl. recess	35 mm
Overall length L	80 mm
Balance quality with shank	G 2.5 with HB
Shank $\varnothing D_s$	10 mm
Cutting edge $\varnothing D_c$	10 mm
Tolerance nominal \varnothing	f8
Shank	DIN 6535 HB to h6
Corner chamfer width at 45°	0.2 mm
Corner chamfer angle	45 °
Number of chip separators	1
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.07×D
Through-coolant	no
Machining strategy	TPC
Colour ring	green
Type of product	End / face mill

User data

	Suitability	V_c	ISO code
Steel < 500 N/mm ²	suitable	380 m/min	P

Steel < 750 N/mm ²	suitable	340 m/min	P
Steel < 900 N/mm ²	suitable	300 m/min	P
Steel < 1100 N/mm ²	suitable	230 m/min	P
Steel < 1400 N/mm ²	suitable	150 m/min	P
TOOLOX 33	suitable	60 m/min	H
TOOLOX 44	suitable	40 m/min	H
HARDOX 500 < 1600 N/mm ²	suitable	25 m/min	H
INOX < 900 N/mm ²	suitable	220 m/min	M
INOX > 900 N/mm ²	Suitable only under restricted conditions	150 m/min	M
Uni	Suitable		
wet maximum	suitable		
dry	suitable only under restricted conditions		
Air	suitable		