

Garant

Solid carbide deburrer, spiral flutes 90°, TiSiN, Ø h6 DC: 12mm



Order data

Order number	208156 12
GTIN	4062406288211
Item class	11X

Description

Version:

Tolerance: **Dimension S = ± 0.2 mm.**

Point angle = ±5 arc minutes.

Deburrer for **universal application** in virtually all materials. The newly developed coating effectively prevents built-up edges, even in aluminium or stainless steel.

Outstanding surface qualities thanks to the 35° **helix angle.**

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications.**

No. of teeth Z: 4

Shank: DIN 6535 HA to h6

Chamfer mill: 45 °

No. of teeth Z: 4

Dimension S: 8.5 mm

Overall length L: 83 mm

Shank Ø D_s: 12 mm

Feed f_z in steel < 900 N/mm²: 0.08 mm

Technical description

Shank Ø D _s	12 mm
Feed f _z in steel < 900 N/mm ²	0.08 mm
Chamfer mill	45 °
Cutting edge Ø D _c	12 mm

Overall length L	83 mm
Dimension S	8.5 mm
Shank	DIN 6535 HA to h6
No. of teeth Z	4
Corner chamfer angle	45 °
Coating	TiSiN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	h6
Helix angle	35 °
Direction of infeed	horizontal and oblique
Countersink tip angle	90 °
Through-coolant	no
Shank tolerance	h6
Colour ring	green
Type of product	Deburrers

User data

	Suitability	V _c	ISO code
Alu plastics	suitable only under restricted conditions	180 m/min	N
Aluminium (short chipping)	suitable	300 m/min	N
Alu > 10% Si	suitable	220 m/min	N
Steel < 500 N/mm ²	suitable	130 m/min	P
Steel < 750 N/mm ²	suitable	115 m/min	P
Steel < 900 N/mm ²	suitable	110 m/min	P
Steel < 1100 N/mm ²	suitable	80 m/min	P

Steel < 1400 N/mm ²	Suitable only under restricted conditions	65 m/min	P
Steel < 55 HRC	Suitable only under restricted conditions	35 m/min	H
INOX < 900 N/mm ²	suitable	90 m/min	M
INOX > 900 N/mm ²	suitable	70 m/min	M
Ti > 850 N/mm ²	suitable	50 m/min	S
GG(G)	suitable	100 m/min	K
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	Suitable only under restricted conditions		
Air	Suitable only under restricted conditions		

Services

Shank grinding Type HB

129100 HB