

Solid carbide copy milling cutter extra long, Plain shank, Ø D: 8mm



Order data

Order number	2125928
GTIN	4045197761446
Item class	210

Description

Version:

Exactly accurate insert bedding due to optimised design of insert and insert seat tolerances. Highest interchange accuracy guaranteed: \pm 0.015 mm. Without through—coolant feed.

Application:

General use for finishing and semi-finishing operations.

Solid carbide – for large depths of cut and to minimise vibration.

Note:

Calculate the speed based on the effective \emptyset D_w. Use GARANT torque screwdriver TQ No.

211750 size 0.9 with bit No. 674252 size 7IP.

Tool exchange: PowerCard Through-coolant: no

Number of cutting edges Z: 2

Overhang L₁: 40 mm

Overall length L_{tot}: 150 mm

Ø d₁: 7.2 mm

Shank Ø D_s h6: 8 mm

Insert screw: 219870 (7IP; 0.9 Nm)

Technical description

Overhang L ₁	40 mm
Overall length L _{tot}	150 mm
Shank Ø D _s h6	8 mm
Insert screw	219870 (7IP; 0.9 Nm)
Number of cutting edges Z	2

$\emptyset d_1$	7.2 mm
Cutting edge Ø D _C	8 mm
Through-coolant	no
Shank type	Plain shank
Milling application	Copy milling
Tool exchange	PowerCard

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 7IP	674252 7IP
Clamping screw	219870
Torque screwdriver, fixed setting set torque 0,9 N·m	211750 0,9