

**Garant**
**SEMT 1305 AGSR, HB7520, Type: UNI**

**Order data**

Order number	213592 UNI
GTIN	4045197806185
Item class	21A

**Description**
**Version:**

Increased insert thickness for the highest metal removal rates. Protected against wear by the latest coating.

**Note:**

Standard application values for  $a_e = 0.5... 1 \times D$  /  $a_{pmax} = 4$  mm.

**Technical description**

Type	UNI
ISO code indexable insert	SEMT 1305 AGSR
Grade	HB7520
Tool material	Carbide
Number of changes/inserts	4
Type of product	Indexable insert for milling

**User data**

	<b>Suitability</b>	<b>V<sub>c</sub></b>	<b>ISO code</b>
Steel < 500 N/mm <sup>2</sup>	suitable	220 m/min	P
Steel < 750 N/mm <sup>2</sup>	suitable	180 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	160 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable	90 m/min	P
Steel < 1400 N/mm <sup>2</sup>	suitable	90 m/min	P
INOX < 900 N/mm <sup>2</sup>	suitable	150 m/min	M
INOX > 900 N/mm <sup>2</sup>	suitable	120 m/min	M
GG(G)	suitable	90 m/min	K
wet maximum	suitable only under restricted conditions		
dry	suitable		