

Softcut® 90° shoulder mill MTC, with threaded shank, \varnothing D / number of teeth Z: 19,7/3mm



Order data

Order number	215570 19,7/3
GTIN	4045197409201
Item class	210

Description

Version:

High precision indexable face mill with irregular pitch for very smooth cutting, very high precision, and very high metal removal rate. **New generation** of high performance indexable face mills with special geometry for reduced cutting forces for MTC applications under unstable conditions or for spindles with low drive power.

Application:

For face milling to large depths, also slotting. General use in all steels including stainless steels.

Spare part:

Pack of insert screws No. 219826 (8IP; 2.2 Nm).

Note:

The insert pocket must be modified when using indexable inserts with a radius greater than 2 mm

GARANT torque screwdriver TQ No. 211750 size 2.2, use bit No. 674252 size 8IP.

Overall length L_{tot}: 30 mm

Ø D₁ h6: 10.5 mm Ø D₂: 17.7 mm

Mounting thread M: M10

Circular interpolation milling \varnothing D_{min}: 36.4 mm Circular interpolation milling \varnothing D_{max}: 37.4 mm

Technical description

Pack of insert screws 219826 (8IP; 2.2 Nm)

Cutting edge Ø D _c	19.7 mm
Mounting thread M	M10
Ø D ₁ h6	10.5 mm
\emptyset D ₂	17.7 mm
Overall length L _{tot}	30 mm
suitable indexable insert	AP 1335
Number of cutting edges Z	3
Circular interpolation milling \emptyset D_{max}	37.4 mm
Circular interpolation milling a _p	1.7 mm
Circular interpolation milling \emptyset D_{min}	36.4 mm
Ramping angle α_{max}	1.21 °
Ramping length L for α_{max}	14.2 mm
Series	Softcut®
\emptyset D ₃	16.7 mm
Shank type	with threaded shank
Setting angle κ	90 °
Milling application	Circular milling
Milling application	Circular milling
Milling application	Ramping
Spacing of the cutters	unequal spacing
Through-coolant	yes
Machining strategy	MTC
Tool exchange	PowerCard
Type of product	End / face mill

Accessories

Torque screwdriver, fixed setting set torque 2,2 N⋅m	211750 2,2
Set of insert screws 10-piece	219826

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 8IP

674252 8IP