

Garant
Side lock arbor Form AD with cooling channel bore, BT 30 short, Clamping Ø D1: 8mm

Order data

Order number	302593 8
GTIN	4045197944542
Item class	31A

Description
Version:

All shanks hard turned (for smooth running). Balancing quality G2.5 / 25,000 rpm. **With coolant supply holes that can be plugged.**

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308760 – 308802. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 50 mm

External Ø D: 28 mm

Spare clamping screw No. 30 9900: 8

Technical description

Overhang dimension A	50 mm
Clamping Ø D ₁	8 mm
Spare clamping screw No. 30 9900	8
External Ø D	28 mm
Adapter	BT 30 short
Standard	DIN 6359
Arbor standard	ISO 7388-2

Arbor standard	JIS B6339
Shape	AD
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Spare clamping screw for chucks with clamping \varnothing D1 8 mm	309900 8
---	----------