



## Side lock arbors Form AD, BT 30 short, Clamping range $\varnothing D_1$ : 12mm



### Order data

Order number	302597 12
GTIN	4062406100094
Item class	32A

### Description

#### Version:

All shanks fine bead blasted. Balancing quality G6.3 / 18,000 rpm.

#### Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

#### Optional extras:

Pull studs (PS) No. 308760 – 308802. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 55 mm

External  $\varnothing D$ : 42 mm

Spare clamping screw No. 30 9900: 12

### Technical description

Spare clamping screw No. 30 9900	12
External $\varnothing D$	42 mm
Overhang dimension A	55 mm
Clamping $\varnothing D_1$	12 mm
Adapter	BT 30 short
Standard	DIN 6359
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339

Shape	AD
Balance quality G at rotational speed	G 6.3 at 18,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Type of product	Side lock arbor

---

## Accessories

Pull stud 45° sealed suitable for steep tapers 30	308765 30
Pull-stud 60° sealed suitable for steep tapers 30	308780 30
Pull stud 45° sealed suitable for steep tapers 30	308760 30
Pull stud 60° sealed suitable for steep tapers 30	308785 30
Spare clamping screw for chucks with clamping $\varnothing$ D1 12 mm	309900 12