

**Garant**
**Face mill arbor vibration damped, BT 40 A = 200, Spigot  $\varnothing$  d1: 16mm**

**Order data**

Order number	303050 16
GTIN	4045197821621
Item class	31A

**Description**
**Version:**

- **Cylindrical form.**
- **Taper shank, spigot, and all contact surfaces are ground at the collar.**
- **With RFID/Balluffchip bore.**
- **Larger collar contact face.**
- **Vibration damped version, arbor with vibration-damping core.**

**Advantage:**

Significantly lower tendency to vibrate. Considerable increase in feed rate.

**Supplied with:**

Cutter lock screw and drive dog.

**Optional extras:**

Special toggle spanner No. 309840.

**Note:**

Further sizes on request.

Overhang dimension A: 200 mm

External  $\varnothing$  D: 38 mm

Milling mandrel length  $L_4$ : 17 mm

**Technical description**

Spigot $\varnothing$ d <sub>1</sub>	16 mm
Overhang dimension A	200 mm
External $\varnothing$ D	38 mm
Milling mandrel length $L_4$	17 mm
Adapter	BT 40 A = 200

Standard	DIN 6357
Arbor standard	DIN 69893
Arbor standard	JIS B6339
Arbor standard	JIS B6339
Shape	A
Balance quality G at rotational speed	G 6.3 at 8,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor

## Accessories

Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Toggle spanner for mandrel Ø 16 mm	309840 16
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Hurco 45° pull stud with 4-mm bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40

Pull stud 45° sealed suitable for steep tapers 40

308760 40