

Garant
Short drill chuck Form ADB, BT 40, Clamping range: 0,5-16mm

Order data

Order number	303175 0,5-16
GTIN	4045197584380
Item class	31B

Description
Version:

For clockwise and anticlockwise rotation.

Concentricity $\leq 20 \mu\text{m}$.

With through coolant feed up to max. 50 bar.

Supplied with:

Clamping wrench.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Concentricity: $\leq 20 \mu\text{m}$

Overhang dimension A: 98 mm

External \varnothing D: 57 mm

Spare chuck key No. 627425: 6 AF

Technical description

Overhang dimension A	98 mm
Spare chuck key No. 627425	6 AF
Clamping range	0.5 - 16 mm
External \varnothing D	57 mm
Adapter	BT 40
Arbor standard	JIS B6339
Arbor standard	ISO 7388-2

Shape	ADB
Through-coolant	yes, with max. 50 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 20 µm
Type of product	Short drill chuck

Accessories

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Hexagon screwdriver, with T-handle Hexagon 6 mm	627481 6
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Hexagon screwdriver with T-handle Hexagon 6 mm	627425 6
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40