

Garant
Shrink-fit chuck Form ADB, BT 40 A = 160, Clamping range \varnothing D1: 12mm

Order data

Order number	303430 12
GTIN	4045197468116
Item class	31A

Description
Version:

- Integral tool length adjustment, range 10 mm (from \varnothing 6).
- Size 3-5 for carbide, from size 6 for HSS and carbide.

Application:

For clamping tools with parallel shank to h6 tolerance.

Standard:

Ähnlich E-DIN 69882-8, Form G.

Optional extras:

Pull studs (PS), No. 308760 – 308806, shrink-fit chuck extension No. 302410 – 302417, shrink-fit units No. 354210 – 354400.

Clamping \varnothing D₁: 12 mm

Overhang dimension A: 160 mm

External \varnothing D: 32 mm

\varnothing D₂: 24 mm

Technical description

\varnothing D ₂	24 mm
Clamping \varnothing D ₁	12 mm
Overhang dimension A	160 mm
External \varnothing D	32 mm
Adapter	BT 40 A = 160

Arbor standard	ISO 7388-2
Arbor standard	JIS B6339
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck

Accessories

Shrink-fit unit Type SU1	354210 SU1
Cooling adapter long 4.5° for clamping Ø 9,1-12 mm	354236 9,1-12
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Basic tool mounting for SK for SK taper shank 40	354225 40
Cooling adapter short 4.5° for clamping Ø 9,1-12 mm	354235 9,1-12
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Subframe cupboard	354290
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Hurco 45° pull stud with 4-mm bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Cooling unit Type CU1	354215 CU1
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40

Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Screening plate for coil SU1 for clamping Ø 6-12 mm	354240 6-12
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40