

## Garant

**High-Performance face mill arbor vibration-damped, cylindrical, with cooling channel bores, HSK-A 63 A = 200, Spigot Ø d1: 22mm**



### Order data

Order number	306692 22
GTIN	4045197945860
Item class	31H

### Description

#### Version:

- Taper shank, spigot, and all contact surfaces are ground at the collar.
- With Balluff/RFID chip bore.
- Increased collar contact surface.

#### Advantage:

The heavy metal core specially matched to the arbors gives optimum machining results even with long overhangs:

- Saves time, because allows use of the maximum machining parameters.
- Smooth running and thus perfect surface quality results.
- Saves costs, because tool life is increased.
- Less vibrational stress on the machine headstock.

#### Supplied with:

Cutter lock screw and drive dog.

#### Optional extras:

Special coolant pipe wrench No. 309840, coolant pipe No. 309880.

#### Note:

Balance quality G 6.3 dependent on the maximum operating speed.

Overhang dimension A: 200 mm

External Ø D: 48 mm

Milling mandrel length L<sub>4</sub>: 19 mm

maximum speed n<sub>max</sub>: 8000 min<sup>-1</sup>

### Technical description

Overhang dimension A	200 mm
Spigot $\varnothing d_1$	22 mm
Milling mandrel length $L_4$	19 mm
External $\varnothing D$	48 mm
maximum speed $n_{\max}$	8000 $\text{min}^{-1}$
Clamping $\varnothing D_1$	22 mm
Adapter	HSK-A 63 A = 200
Standard	DIN 6357
Arbor standard	DIN 69882-3
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	A
Concentricity	$\leq 5 \mu\text{m}$
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor