

**Garant**
**Short drill chuck Form A, HSK-A 100, Clamping range: 1-16mm**

**Order data**

Order number	307735 1-16
GTIN	4045197931894
Item class	31B

**Description**
**Version:**

- **For clockwise and anticlockwise rotation.**
- **With RFID/Balluffchip bore.**

With through coolant feed up to max. 50 bar.

Concentricity  $\leq 20 \mu\text{m}$ .

- **Slim design.**
- **Specific coolant transfer to tools with IC.**
- **Optimum holding torques at the tool.**

**Supplied with:**

**Clamping wrench** with T-handle.

**Optional extras:**

Socket wrench No. 309890. Coolant tube No. 309880.

Type: slim

Overhang dimension A: 110 mm

External  $\varnothing$  D: 50 mm

Spare Torx® chuck key No. 625220: TX25

**Technical description**

Spare Torx® chuck key No. 625220	TX25
External $\varnothing$ D	50 mm
Overhang dimension A	110 mm

Clamping range	1 - 16 mm
Type	slim
Adapter	HSK-A 100
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-7
Arbor standard	DIN 69893-1
Shape	A
Through-coolant	yes, with max. 50 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 20 μm
Type of product	Short drill chuck