



## Short drill chuck Form A, HSK-A 100, Clamping range: 2,5-16mm



### Order data

Order number	307775 2,5-16
GTIN	4045197932013
Item class	32K

### Description

#### Version:

- For clockwise and anticlockwise rotation.
- With Ballufchip bore.
- Slim design.
- Specific coolant transfer to tools with IC.
- Optimum holding torques at the tool.

#### Supplied with:

Clamping wrench with T-handle.

#### Optional extras:

Socket wrench No. 309890. Coolant tube No. 309880.

Type: slim

Overhang dimension A: 110 mm

External Ø D: 50 mm

Spare Torx® chuck key No. 625220: TX25

### Technical description

Overhang dimension A	110 mm
Clamping range	2.5 - 16 mm
Spare Torx® chuck key No. 625220	TX25
External Ø D	50 mm

Type	slim
Adapter	HSK-A 100
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-7
Arbor standard	DIN 69893-1
Shape	A
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	$\leq 50 \mu\text{m}$
maximum tightening torque $M_{d \max}$	$\leq 14 \text{ N}\cdot\text{m}$
Type of product	Short drill chuck