



## Pull stud sealed, with bore, suitable for steep tapers: 40



### Order data

Order number	308635 40
GTIN	4045197644480
Item class	32Z

### Description

#### Description:

The toolholder is securely pulled into the spindle by the spindle's clamping gripper using the pull stud. Pull studs come in different versions. They are an important link between the machine and tool. Stringent requirements apply for the accuracy, strength and reliability of pull studs.

#### Application:

- For tools with taper shanks see also DIN 69871 and JIS B 6339 (MAS-BT).
- In machining centres (machines with automatic tool changers).
- In NC machines (machines without automatic tool changers).

#### Suitable for :

FADAL, similar to ISO 7388, 3 mm, extended.

#### Note:

Look in the eShop – you will find the right clamping wrench and width for every job.

When installing the pull stud, cheque the correct tightening torque.

**Sealed** – with O-ring. No suitable chuck key available.

Pull stud standard: ISO 7388-3

Collar Ø D: 22 mm

Head Ø D<sub>1</sub>: 18.95 mm

Overall length L: 47.5 mm

L<sub>1</sub>: 19.25 mm

Thread M: M16

maximum tightening torque: 50 N·m

### Technical description

L <sub>1</sub>	19.25 mm
Collar Ø D	22 mm
suitable for taper arbors with colour code	SK 40
Head Ø D <sub>1</sub>	18.95 mm
maximum tightening torque	50 N·m
Thread M	M16
suitable for steep tapers	40
Overall length L	47.5 mm
Width across flats	19 mm
Hole characteristics	with bore
Pull stud standard	ISO 7388-3
Type of product	Pull Stud