



Pull stud sealed, form B, with bore, suitable for steep tapers: 40



Order data

Order number	308650 40
GTIN	4045197150981
Item class	32Z

Description

Description:

The toolholder is securely pulled into the spindle by the spindle's clamping gripper using the pull stud. Pull studs come in different versions. They are an important link between the machine and tool. Stringent requirements apply for the accuracy, strength and reliability of pull studs.

Application:

- For tools with taper shanks see also DIN 69871 and JIS B 6339 (MAS-BT).
- In machining centres (machines with automatic tool changers).
- In NC machines (machines without automatic tool changers).

Note:

Sealed – with O-ring.

Look in the eShop – you will find the right clamping wrench and width for every job.

When installing the pull stud, cheque the correct tightening torque.

Pull stud standard: ISO 7388

Collar Ø D: 22.5 mm

Head Ø D₁: 18.95 mm

Overall length L: 44.5 mm

L₁: 16.25 mm

Thread M: M16

maximum tightening torque: 50 N·m

Technical description

Overall length L	44.5 mm
------------------	---------

suitable for taper arbors with colour code	SK 40
Head Ø D ₁	18.95 mm
Thread M	M16
Collar Ø D	22.5 mm
L ₁	16.25 mm
suitable for steep tapers	40
maximum tightening torque	50 N·m
Width across flats	18 mm
Hole characteristics	with bore
Pull stud standard	ISO 7388
Type of product	Pull Stud

Accessories

Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40