



## Special pull stud S20×2, suitable for steep tapers: 40



### Order data

|              |               |
|--------------|---------------|
| Order number | 308800 40     |
| GTIN         | 4045197151094 |
| Item class   | 32Z           |

### Description

#### Description:

The toolholder is securely pulled into the spindle by the spindle's clamping gripper using the pull stud. Pull studs come in different versions. They are an important link between the machine and tool. Stringent requirements apply for the accuracy, strength and reliability of pull studs.

#### Note:

Look in the eShop – you will find the right clamping wrench and width for every job. When installing the pull stud, cheque the correct tightening torque.

Overall length L: 53 mm

L<sub>1</sub>: 25 mm

Thread M: M16

Thread M<sub>1</sub>: S20×2

maximum tightening torque: 50 N·m

suitable for taper arbors with colour code: SK 40

### Technical description

|  |        |
|--|--------|
| maximum tightening torque                  | 50 N·m |
| L <sub>1</sub>                             | 25 mm  |
| Thread M                                   | M16    |
| suitable for taper arbors with colour code | SK 40  |
| suitable for steep tapers                  | 40     |
| Overall length L                           | 53 mm  |

|                       |           |
|-----------------------|-----------|
| Thread M <sub>1</sub> | S20×2     |
| Type of product       | Pull Stud |