HOLEX

Digital caliper IP67, Measuring range: 150mm



Order data

| Order number | 412751 150 |
|--------------|---------------|
| GTIN | 4045197347411 |
| Item class | 42A |

Description

Version:

Large high-contrast digital display. The measuring faces are precision-lapped. The caliper is resistant to water and dust. After 2 hours without movement, the control system shuts down the caliper automatically. Shock-resistant plastic casing.

Standard:

Clearly legible, high-contrast digital display. The calliper is resistant to water, coolant, oil, and dust. The measuring faces are precision lapped.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Battery No. 081560 size CR2032. Packaging: sturdy box Standard: ISO 13385 Reversible reading: mm / inch Depth gauge: rectangular 3.7×1.3 IP Index of Protection: IP 67 Calibration: A1 Scale divisions: 0.01 mm Scale divisions: 0.0005 in Jaw length: 40 mm

Technical description

Material of the housing

Plastic

| Depth gauge available | yes |
|---|-----------------------|
| Calibration | A1 |
| Reversible reading | mm / inch |
| Jaw length | 40 mm |
| Depth gauge | rectangular 3.7×1.3 |
| Auto switch-off | yes |
| Standard | ISO 13385 |
| Scale divisions | 0.01 mm |
| Scale divisions | 0.0005 in |
| Measuring range | 0 - 150 mm |
| Article no of the battery / rechargeable battery fitted | 081560 CR2032 |
| Number of batteries contained | 1 |
| IP Index of Protection | IP 67 |
| Power supply | Battery-powered |
| Measurement deviation E MPE | ± 0.03 mm |
| Measurement technology | digital |
| Material | Stainless steel, INOX |
| all parts | hardened |
| Packaging | sturdy box |
| Type of product | Universal calipers |

Services

| Calibration Calipers / depth gauges maximum measuring range 200 mm | 011030 200 |
|--|------------|
| Labelling laser-etched Type | 018940 |
| DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm | 011050 200 |
| Calibration Calipers / depth gauges maximum measuring range 200 mm | 021000 200 |
| | 021010 200 |

DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm

Accessories

| Screw for depth gauge holder | 412230 |
|---|---------------|
| Button cell / special battery Battery type CR2032 | 081560 CR2032 |
| Plastic case Type MS150 | 412468 MS150 |
| Plastic case Type MS150 | 412470 MS150 |