


**TMSERROR, Measuring range: 150mm**

**Order data**

Order number	412812 150
GTIN	4045197422828
Item class	42A

**Description**
**Version:**

Large, sharp-contrast digital display. The measuring faces are precision-lapped.  
With plastic housing, **for left-handed use.**

**Supplied with:**

Battery No. 081560 size LR44.  
Packaging: sturdy box  
Standard: ISO 13385  
Reversible reading: mm / inch  
Depth gauge: rectangular 3.7×1.3  
Calibration: A1  
Scale divisions: 0.01 mm  
Scale divisions: 0.0005 in  
Jaw length: 40 mm

**Technical description**

Material of the housing	Plastic
Standard	ISO 13385
Jaw length	40 mm
Reversible reading	mm / inch
suitable for left-handed use	yes
Calibration	A1

Depth gauge	rectangular 3.7×1.3
Depth gauge available	yes
Scale divisions	0.01 mm
Scale divisions	0.0005 in
Measuring range	0 - 150 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 LR44
Power supply	Battery-powered
Measurement deviation E MPE	±0.03 mm
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	sturdy box
Type of product	Universal calipers

## Services

Calibration Calipers / depth gauges maximum measuring range 200 mm	011030 200
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	011050 200
DAkkS calibration Calipers / depth gauges maximum measuring range 200 mm	021010 200
Calibration Calipers / depth gauges maximum measuring range 200 mm	021000 200

## Accessories

Button cell / special battery Battery type LR44	081560 LR44
---	-------------