



External micrometer, Measuring range: 0-25mm



Order data

Order number	420200 0-25
GTIN	4045197203762
Item class	42B

Description

Version:

Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle.

Locking by clamping lever.

With ratchet and hand temperature protection.

With clearly engraved, black divisions and numerals.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 2 μ m

Spindle \varnothing : 6.5 mm

Barrel \varnothing : 18 mm

Technical description

Measuring range	0 - 25 mm
Spindle \varnothing	6.5 mm
Barrel \varnothing	18 mm
Micrometer barrel graduations	1/50 mm

Scale divisions	0.01 mm
Calibration	B1
Error limit	2 μ m
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 25 mm	022000 25
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100