



External micrometer, Measuring range: 0-25mm



Order data

Order number	420430 0-25
GTIN	4062406237509
Item class	42B

Description

Version:

Precision lapped, carbide-tipped measuring faces.

Hardened and ground measuring spindle. Locking by clamping lever.

With ratchet and hand temperature protection. Barrel non-reflecting chrome-plated.

With clearly engraved, black divisions and numerals.

With combined sensitive ratchet for one-hand operation and operation within the bracket.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Standard: DIN 863

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Scale divisions: 0.01 mm

Spindle \varnothing : 6.5 mm

Barrel \varnothing : 20.5 mm

Technical description

Measuring range	0 - 25 mm
Calibration	B1
Scale divisions	0.01 mm
Barrel \varnothing	20.5 mm

Spindle Ø	6.5 mm
Micrometer barrel graduations	1/50 mm
Standard	DIN 863
Ratchet	yes
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 25 mm	012050 25
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration External tube micrometer maximum measuring range 25 mm	022000 25