

**External blade micrometer, Measuring range: 75-100mm****Order data**

| | |
|--------------|---------------|
| Order number | 421900 75-100 |
| GTIN | 4045197203984 |
| Item class | 42B |

Description**Version:**

With non-rotating spindle and flat blade anvils. Measuring spindle and anvil of hardened steel, controls and reading parts satin chrome-plated.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Scale divisions: 0.01 mm

Spindle Ø: 8 mm

Spindle pitch: 0.5 mm

Flat blade anvils width: 0.75 mm

Flat blade anvils length: 6.5 mm

Technical description

| | |
|-------------------------------|-------------|
| Measuring range | 75 - 100 mm |
| Flat blade anvils width | 0.75 mm |
| Micrometer barrel graduations | 1/50 mm |
| Spindle Ø | 8 mm |
| Flat blade anvils length | 6.5 mm |

| | |
|------------------------|---------------------|
| Spindle pitch | 0.5 mm |
| Scale divisions | 0.01 mm |
| Calibration | B2 |
| Standard | DIN 863 |
| Measurement technology | analogue |
| Packaging | sturdy box |
| Type of product | External micrometer |

Services

| | |
|--|------------|
| Labelling laser-etched Type | 018940 |
| Calibration External micrometer including setting dimension maximum measuring range 100 mm | 022040 100 |
| DAkkS calibration External micrometer including setting dimension maximum measuring range 100 mm | 022050 100 |

Accessories

| | |
|--|-----------|
| Micrometer setting standard overall length 75 mm | 421100 75 |
|--|-----------|