



## Depth gauge with analogue dial indicator, Measuring range: 10mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 434805 10     |
| GTIN         | 4045197234124 |
| Item class   | 42C           |

### Description

#### Version:

Hardened base with fine lapped contact surface. Dial indicator securely clamped by collet. **Dial indicator with anticlockwise scale measuring depth can be read off directly.** Greater depths can be measured using extension rods of differing lengths(see No. 434920).

#### Supplied with:

Dial indicator No. 434807 size 10 or 30.

#### Optional extras:

Extension for No. 434920.

Packaging: sturdy box

Calibration: C8

Calibration: C1

Graduation: 0.01 mm

Reading per pointer revolution: 1 mm

Variation range  $f_e$ : 15  $\mu$ m

Probe plunger  $\varnothing$ : 4 mm

Bridge length: 80 mm

Bridge width: 16 mm

### Technical description

|                                |                         |
|--------------------------------|-------------------------|
| Reading per pointer revolution | 1 mm                    |
| Measuring range                | 10 mm                   |
| Dial indicator Ø               | 58 mm                   |
| Bridge width                   | 16 mm                   |
| Bridge length                  | 80 mm                   |
| Probe plunger Ø                | 4 mm                    |
| Calibration                    | C8                      |
| Calibration                    | C1                      |
| Variation range $f_e$          | 15 µm                   |
| Graduation                     | 0.01 mm                 |
| Standard                       | Manufacturer's standard |
| Measurement technology         | analogue                |
| Packaging                      | sturdy box              |
| Type of product                | Depth gauge             |

## Services

|  |             |
|--|-------------|
| Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 10 mm         | 013210 10   |
| Calibration Measurement head Type MU   | 012580 MU   |
| Labelling laser-etched Type  | 018940      |
| DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm | 013250 12,5 |
| Calibration Measurement head Type B  | 023360 B    |
| Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 10 mm         | 023000 10   |
| DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm | 023010 12,5 |

## Accessories

|   |                |
|---|----------------|
| Extension for measuring probe Length L 60 mm                  | 434920 60      |
| Extension for measuring probe Length L 90 mm                  | 434920 90      |
| Knurled nut Thread M14X0,5                                    | 434806 M14X0,5 |
| Extension for measuring probe Length L 100 mm                 | 434920 100     |
| Extension for measuring probe Length L 80 mm                  | 434920 80      |
| Extension for measuring probe Length L 40 mm                  | 434920 40      |
| Extension for measuring probe Length L 10 mm                  | 434920 10      |
| Extension for measuring probe Length L 50 mm                  | 434920 50      |
| Extension for measuring probe Length L 15 mm                  | 434920 15      |
| Extension for measuring probe Length L 20 mm                  | 434920 20      |
| Dial indicator with anticlockwise scale Measuring range 10 mm | 434807 10      |
| Extension for measuring probe Length L 70 mm                  | 434920 70      |
| Extension for measuring probe Length L 30 mm                  | 434920 30      |