

Garant
Hydraulic jointed measuring stand (without magnetic base), Throat: 400mm

Order data

| | |
|--------------|---------------|
| Order number | 440610 400 |
| GTIN | 4045197889591 |
| Item class | 41D |

Description
Version:

Hydraulic measuring stand with central clamping - all joints are rigidly clamped by means of the central rotary knob. Oil hydraulics protected against oil leakage by double seals. Clamping force can be steplessly adjusted. **Large rubberised hand wheel** (Ø 54 mm) for easy tightening and releasing the clamp. Jointed arms on the dial indicator mounting rotates 360°, can be twisted 180° and suitable for dial indicators with shank Ø 6 and 8 mm or dovetail.

Callout:
Hydraulic central locking

with ergonomic handwheel

Fine adjustment

at the indicator holder

Ball joint
Magnetic base

in a plastic enclosure

Note:

Hydraulic stands can withstand large fluctuations in temperature when the clamp is open. However a certain time is required for the temperature of the oil to equalise. When the clamp is closed the maximum fluctuation in temperature without fluctuations in pressure is 15 °C. These can lead to damage to the stand or to the object that is clamped.

Throat: 400 mm

Connection thread: M8 external thread

Magnetic force: 1000 N

Technical description

| | |
|-------------------|--------------------|
| Throat | 400 mm |
| Connection thread | M8 external thread |
| Magnetic force | 1000 N |
| Type of product | measuring stand |

Accessories

| | |
|---|----------|
| Replacement handwheel Type A | 440626 A |
| Spare piston Type 4 | 440830 4 |
| Clamping handle Type 4 | 440850 4 |
| Clamping screw M3 for dial indicator clamp | 440858 |
| Adjustment screw M4×0.35 for dial indicator clamp | 440859 |
| Dial indicator clamp | 440860 |
| Sealing ring set Type 1 | 440855 1 |