

## Single test pin Tolerance class 2, Type: 9



### Order data

Order number	483910 9
GTIN	2050001048981
Item class	48A

### Description

#### IMPORTANT: item is configurable

Nominal size: 19 - 20 mm, Intervall: 0,010

#### Version:

Of high quality gauge steel, hardened ( $60 \pm 2$  HRC) and tempered. Surface ground and lapped. From  $\varnothing$  1.5 mm engraved with the size, 0.1 mm – 0.99 mm without a chamfer. From 1.0 mm one end chamfered.

**Tolerance class 2:** Pin  $\varnothing \pm 0.002$  mm.

#### Application:

Degrease before use and grease after use.

#### Note:

When ordering, please additionally state the **desired  $\varnothing$** , e.g. No. 483900 size 5 **10.08** or 483920 size 5 **10.082**.

Calibration: L5

Nominal size: 19 - 20 mm

Pitch: 0.01 mm

Gauging pin length: 70 mm

### Technical description

Pitch	0.01 mm
Gauging pin length	70 mm
Nominal size	19 - 20 mm
Standard	DIN 2269
Tolerance class	2
Hardness	$60 \pm 2$ HRC

Material	Gauge steel
Calibration	L5
Type of product	Test pin

**Services**

Calibration Test pin Type	018380
DAkkS calibration Test pin Type	018650
Calibration Test pin maximum Ø 20	028240 20
DAkkS calibration Test pin maximum Ø 20	028260 20
Labelling laser-etched Type	018940