

## “Go” / “No Go” gauge with intermediate sizes and ISO fits with wear allowance, Type: B



### Order data

|              |               |
|--------------|---------------|
| Order number | 484025 B      |
| GTIN         | 4045197211781 |
| Item class   | 48B           |

### Description

#### IMPORTANT: item is configurable

Tolerance zone: A; B; C; CD; D; E; EF; F; FG; G; H; J; JS; K; M; N; P; R; S; T; U; V; X; Y; Z; ZA; ZB; ZC

Quality: 10; 11; 12; 13; 6; 7; 8; 9

Nominal size: 3 - 10 mm, Intervall: 0,001

#### Version:

Measuring body made of first class gauge steel, hardened, stress-relieved, ground, and lapped. The “Go” ends of these working gauges have a wear allowance to DIN 7164.

“Go” / “No Go” plug gauges with intermediate sizes and ISO fits, e.g. No. 484025 **2.37 H6**.

#### Standard:

Toleranz und Abmaße nach **DIN 1938-1, DIN 2245-1 und DIN 7164**.

#### Note:

- **Please state the exact nominal  $\varnothing$  with tolerance band (A-ZC) and quality (6-13) or numeric tolerance ( $\pm$ ).**
- **Intermediate size plug gauges are just double-ended plug gauges in fractional sizes!**
- **For whole number (even)  $\varnothing$  with ISO fits see No. 484000; 484020; 484040 or on request.**
- **For acceptance gauges (without wear allowance) see No. 484027; 484028.**

Calibration: L6

Nominal size: 3 - 10 mm

### Technical description

|                |   |
|----------------|---|
| Tolerance zone | A |
| Tolerance zone | G |
| Tolerance zone | H |

|                |            |
|----------------|------------|
| Tolerance zone | J          |
| Tolerance zone | K          |
| Tolerance zone | M          |
| Tolerance zone | N          |
| Tolerance zone | P          |
| Tolerance zone | R          |
| Tolerance zone | S          |
| Tolerance zone | B          |
| Tolerance zone | T          |
| Tolerance zone | U          |
| Tolerance zone | V          |
| Tolerance zone | X          |
| Tolerance zone | Y          |
| Tolerance zone | Z          |
| Tolerance zone | ZA         |
| Tolerance zone | C          |
| Tolerance zone | D          |
| Tolerance zone | E          |
| Tolerance zone | F          |
| Tolerance zone | JS         |
| Tolerance zone | CD         |
| Tolerance zone | EF         |
| Tolerance zone | FG         |
| Tolerance zone | ZC         |
| Tolerance zone | ZB         |
| Standard       | DIN 7150-2 |
| Standard       | DIN 7164   |
| Quality        | 13         |
| Quality        | 11         |

|                 |                 |
|-----------------|-----------------|
| Quality         | 6               |
| Quality         | 12              |
| Quality         | 10              |
| Quality         | 8               |
| Quality         | 7               |
| Quality         | 9               |
| Type of gauge   | "Go" plug gauge |
| Type of gauge   | "No Go" gauge   |
| Nominal size    | 3 - 10 mm       |
| Calibration     | L6              |
| Type of product | Pug Gauge       |

## Services

|   |           |
|---|-----------|
| Calibration "Go" / "No Go" plug gauge maximum $\varnothing$ 20 mm       | 018400 20 |
| Labelling laser-etched Type   | 018940    |
| DAkkS calibration "Go" / "No Go" plug gauge maximum $\varnothing$ 60 mm | 019620 60 |
| DAkkS calibration "Go" / "No Go" plug gauge maximum $\varnothing$ 60 mm | 028340 60 |
| Calibration "Go" / "No Go" plug gauge maximum $\varnothing$ 20 mm       | 028300 20 |