

Setting ring with intermediate sizes, Type: I



Order data

Order number	484035 I
GTIN	4045197212498
Item class	48B

Description

IMPORTANT: item is configurable

Tolerance zone: JS

Nominal size: 60.001 - 69.999 mm, Intervall: 0,001

Quality: 4

Version:

Setting rings (checking rings) of first class gauge steel, hardened, stress-relieved, ground and lapped. **Each setting ring is engraved with the actual size.** Manufacturer's tolerance for the bore is JS4.

Standard:

Nach **DIN 2250 C.**

Note:

Please state the exact nominal \varnothing .

Intermediate size rings are only setting rings with **fractional sizes!**

For whole number (even) \varnothing see 484030 or on request.

Ordering example: \varnothing 10.002: No. 484035 B **10.002.**

Ceramic setting rings with **whole number millimetre sizes** on request.

Not available in intermediate sizes.

Calibration: L7

Nominal size: 60.001 - 69.999 mm

Technical description

Tolerance zone	JS
Nominal size	60.001 - 69.999 mm
Standard	DIN 2250 C
Material	Gauge steel
Manufacturing tolerance of the bore	JS4
Quality	4
Calibration	L7
Type of product	setting ring

Services

Calibration Setting ring maximum \varnothing 100 mm	018430 100
Labelling laser-etched Type	018940
DAkkS calibration Setting ring maximum \varnothing 200 mm	019660 200
Calibration Setting ring maximum \varnothing 100 mm	028400 100
DAkkS calibration Setting ring maximum \varnothing 200 mm	028470 200