

Abrasive cap (CER), 80 grit, Abrasive cap Ø, length, form: 1317A



Order data

Order number	553035 1317A		
GTIN	4062406122713		
Item class	51E		

Description

Version:

Optimised grit bonding yields very aggressive abrasion and a high material removal rate. **Ceramic grit (CER)** ideal for working on stainless steels and nickel alloys. High removal rate and cool cut.

Application:

The seamlessly formed abrasive caps slide on to the rubber body and are securely held in place by centrifugal force when the machine is running. The **abrasive caps can be replaced quickly and easily** (replace in direction of slots).

Note:

Compatible only for use with ground abrasive cap holder No. 553100.

Shape: A

Abrasive cap \varnothing : 13 mm Abrasive cap length: 17 mm

recommended speed: 16000 min⁻¹

Technical description

Abrasive cap Ø	13 mm
----------------	-------

Abrasive cap length	17 mm		
recommended speed	16000 min ⁻¹		
Shape	Α		
Grit	80		
Product name attribute	80 grit		
Type of product	Abrasive cap		

User data

	Suitability	V _c	ISO code
Alu Mg	suitable only under restricted conditions		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable only under restricted conditions		
CuZn	suitable only under restricted conditions		
dry	suitable		