

Abrasive cap (CER), 150 grit, Abrasive cap Ø, length, form: 0511G



Order data

Order number	553038 0511G		
GTIN	4062406122720		
Item class	51E		

Description

Version:

Optimised grit bonding yields very aggressive abrasion and a high material removal rate. **Ceramic grit (CER)** ideal for working on stainless steels and nickel alloys. High removal rate and cool cut.

Application:

The seamlessly formed abrasive caps slide on to the rubber body and are securely held in place by centrifugal force when the machine is running. The **abrasive caps can be replaced quickly and easily** (replace in direction of slots).

Note:

Compatible only for use with ground abrasive cap holder No. 553100.

Shape: G

Abrasive cap Ø: 5 mm Abrasive cap length: 11 mm

recommended speed: 40000 min⁻¹

Technical description

Shape	G

recommended speed	40000 min ⁻¹		
Abrasive cap length	11 mm		
Abrasive cap Ø	5 mm		
Grit	150		
Product name attribute	150 grit		
Type of product	Abrasive cap		

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable only under restricted conditions		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable only under restricted conditions		
CuZn	suitable only under restricted conditions		
dry	suitable		