

**Abrasive sleeve, conical (CER) 80 grit medium, largest sleeve Ø× sleeve width: 20X63mm****Order data**

| | |
|--------------|---------------|
| Order number | 553877 20X63 |
| GTIN | 4045197723338 |
| Item class | 52E |

Description**Version:**

Made of non-tearing, synthetic resin bonded material with long service life and good grit adhesion.

Ceramic grit (CER).

The rubber body of the abrasive sleeve holder expands at high speed to hold the abrasive sleeve in place. The full width of the sleeve can be used, it does not slip and can be replaced quickly and easily (twist in the direction of slots when fitting/removing). Only compatible with abrasive sleeve holders.

Application:

Abrasive sleeves are predominantly used for surface grinding tasks which require the removal of large amounts of material – even at sharp edges.

Suitable for :

Abrasive sleeve holder No. 553830.

Grinding medium code: Ceramic

Technical description

| | |
|------------------|--------------|
| largest sleeve Ø | 20 mm |
| Grit | 80 |
| Sleeve width | 63 mm |
| Grit designation | medium |
| Grinding media | Ceramic grit |

| | |
|----------------------|-----------------|
| Grinding medium code | Ceramic |
| Sleeve shape | conical |
| Type of product | Abrasive sleeve |

User data

| | Suitability | V _c | ISO code |
|--------------------------------|-------------------------------------------|----------------|----------|
| Alu Mg | suitable only under restricted conditions | | |
| Steel < 900 N/mm ² | suitable | | |
| Steel < 1400 N/mm ² | suitable | | |
| Steel < 55 HRC | suitable | | |
| Steel < 60 HRC | suitable | | |
| Steel < 67 HRC | suitable | | |
| INOX | suitable | | |
| Ti | suitable | | |
| GG(G) | suitable | | |
| CuZn | suitable | | |
| Plastic, GRP | suitable | | |
| dry | suitable | | |

Accessories

Abrasive sleeve holder slit, conical shank 6 mm Ø largest Øxhead length 20X63 mm

553830 20X63