

**Garant****Coarse cleaning disc (SiC), Ø 76.2 mm, Fleece version: CRS****Order data**

|              |               |
|--------------|---------------|
| Order number | 554051 CRS    |
| GTIN         | 4062406300975 |
| Item class   | 51E           |

**Description****Version:**

Coarse cleaning disc with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad. Open structure, will not clog. **High material removal rate** for general-purpose cleaning work.

**Application:**

For rust removal, paint removal, dressing weld seams and removing surface dirt.

Iron, sulphur and chlorine constituents: < 0.1 %

Grit designation: extra coarse

Degree of hardness: hard

maximum speed: 15000 min<sup>-1</sup>

**Technical description**

|                    |                         |
|--------------------|-------------------------|
| maximum speed      | 15000 min <sup>-1</sup> |
| Degree of hardness | hard                    |
| Disc Ø             | 76.2 mm                 |
| Grit designation   | extra coarse            |
| Grinding media     | Silicon carbide (SiC)   |

|   |  |
|---|--|
| Grinding medium code                    | SiC                                    |
| Iron, sulphur and chlorine constituents | < 0.1 %                                |
| Product name attribute                  | Ø 76.2 mm                              |
| Type of product                         | Rough cleaning non-woven abrasive mesh |

## User data

|                                | Suitability                               | V <sub>c</sub> | ISO code |
|--------------------------------|---|----------------|----------|
| Alu Mg                         | suitable                                  |                |          |
| Steel < 900 N/mm <sup>2</sup>  | suitable                                  |                |          |
| Steel < 1400 N/mm <sup>2</sup> | suitable                                  |                |          |
| Steel < 55 HRC                 | suitable                                  |                |          |
| Steel < 60 HRC                 | suitable                                  |                |          |
| Steel < 67 HRC                 | suitable                                  |                |          |
| INOX                           | suitable                                  |                |          |
| Ti                             | suitable                                  |                |          |
| GG(G)                          | suitable                                  |                |          |
| CuZn                           | suitable                                  |                |          |
| Plastic, GRP                   | suitable                                  |                |          |
| Wood                           | suitable                                  |                |          |
| Stone                          | suitable only under restricted conditions |                |          |
| Paint                          | suitable                                  |                |          |
| Uni                            | suitable                                  |                |          |
| wet maximum                    | suitable only under restricted conditions |                |          |
| dry                            | suitable                                  |                |          |