

Fleece abrasive finishing disc, Ø 50.8 mm, Grit equivalent: 280



Order data

Order number	554052 280
GTIN	4045197525932
Item class	52E

Description

Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

High performance general-purpose nylon fleece.

Application:

For cleaning, degreasing, and matt finishing of metal surfaces.

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Iron, sulphur and chlorine constituents: < 0.1 %

maximum speed: 23000 min⁻¹

Grit designation: fine Version: A very fine

Technical description

Grit equivalent	280



Version	A very fine	
Grit designation	fine	
Disc Ø	50.8 mm	
Grinding media	Nylon fleece	
Grinding medium code	Α	
Iron, sulphur and chlorine constituents	< 0.1 %	
Product name attribute	Ø 50.8 mm	
maximum speed	23000 min ⁻¹	
Type of product	Non-woven abrasive	

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Stone	suitable only under restricted conditions		
Paint	suitable		
Uni	suitable		



wet maximum	suitable only under restricted conditions	
dry	suitable	

Accessories

Rubber backing pad shank \varnothing 6 mm medium External \varnothing 50 mm	554092 50
Rubber backing pad shank Ø 6 mm soft External Ø 50 mm	554091 50
Rubber backing pad shank Ø 6 mm hard External Ø 50 mm	554089 50
Rubber backing pad shank \varnothing 6 mm medium hard External \varnothing 50 mm	554093 50
Plastic backing pad shank Ø 6 mm External Ø 50 mm	554090 50