

Coarse cleaning disc (SiC), Disc Ø: 150mm



Order data

Order number	555946 150
GTIN	4062406123932
Item class	52E

Description

Version:

Coarse cleaning disc with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad. Open structure, will not clog.

High material removal rate for general-purpose cleaning work.

Application:

For radial use on flexible shafts and straight die grinders. For rust removal, paint removal, dressing weld seams and removing surface dirt.

Iron, sulphur and chlorine constituents: < 0.1 %

Grit designation: extra coarse

Bore Ø: 13 mm Thickness: 15 mm Bore Ø: 13 mm

recommended speed: 4000 min⁻¹

Technical description

recommended speed	4000 min ⁻¹
Disc Ø	150 mm

Bore Ø	13 mm		
Thickness	15 mm		
Grinding media	Silicon carbide (SiC)		
Grinding medium code	SiC		
Degree of hardness	hard		
Grit designation	extra coarse		
Iron, sulphur and chlorine constituents	< 0.1 %		
Type of product	Rough cleaning non- woven abrasive mesh		

User data

	Suitability	V _c	ISO code
Alu Mg	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Stone	suitable only under restricted conditions		
Paint	suitable		
Uni	suitable		
wet maximum	suitable only under restricted conditions		

dry suitable

Accessories

Mandrel Number of discs to be clamped 1-2	556380 1-2
Mandrel Number of discs to be clamped 1	556380 1