



## Abrasive fleece pad, 152×229 mm, Fleece structure: 220



### Order data

Order number	556015 220
GTIN	4045197525871
Item class	52M

### Description

#### Version:

Synthetic nylon fleece impregnated with abrasive grit in synthetic resin bonding.

#### Advantage:

- **Adapts to the component shape.**
- **The open structure prevents clogging and reduces heat development.**
- **Even and reproducible finish.**
- **Can be used wet or dry.**
- **Contains no materials that could cause corrosion.**

#### Application:

Can be used by hand, on hand block No. 556020 or on an orbital sander. **Medium / medium fine:** Can be used universally for removing rust film, light soiling, discolouration; for rubbing down ground or brushed surfaces, or for degreasing and cleaning prior to painting.

Iron, sulphur and chlorine constituents: < 0.1 %

Grit equivalent: 240 - 280

Grit designation: medium

Version: A Fine

Colour: green

### Technical description

Grit equivalent	240 - 280
Fleece structure	220
Grit designation	medium

Colour	green
Version	A Fine
Iron, sulphur and chlorine constituents	< 0.1 %
Width	152 mm
Length	229 mm
Product name attribute	152x229 mm
Type of product	Abrasive fleece pad

## User data

	Suitability	V <sub>c</sub>	ISO code
Alu Mg	suitable		
Steel < 900 N/mm <sup>2</sup>	suitable		
Steel < 1400 N/mm <sup>2</sup>	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Stone	suitable only under restricted conditions		
Paint	suitable		
Uni	suitable		
wet maximum	suitable only under restricted conditions		
dry	suitable		

---

**Accessories**

Mandrel	556030
Hand block	556020