

### Roll of abrasive fleece, 100 mm $\times$ 10 m, Fleece structure: 220



## **Order data**

Order number	556110 220
GTIN	4045197557278
Item class	52M

### **Description**

#### **Version:**

Synthetic nylon fleece impregnated with abrasive grit in synthetic resin bonding.

#### **Advantage:**

- · Adapts to the component shape.
- · The open structure prevents clogging and reduces heat development.
- Even and reproducible finish.
- · Can be used wet or dry.
- · Contains no materials that could cause corrosion.

#### **Application:**

Can be used by hand, on hand block No. 556020 or on an orbital sander. **Medium / medium fine:** Can be used universally for removing rust film, light soiling, discolouration; for rubbing down ground or brushed surfaces, or for degreasing and cleaning prior to painting.

Iron, sulphur and chlorine constituents: < 0.1 %

Grit equivalent: 240 - 280 Grit designation: medium

Version: A Fine Colour: green

## **Technical description**



Grit designation	medium	
Colour	green	
Fleece structure	220	
Grit equivalent	240 - 280	
Version	A Fine	
Iron, sulphur and chlorine constituents	< 0.1 %	
Roller width	100 mm	
Roll length	10 m	
Product name attribute	100 mm × 10 m	
Type of product	Roll of abrasive fleece	

# **User data**

	Suitability	<b>V</b> <sub>c</sub>	ISO code
Alu Mg	suitable		
Steel < 900 N/mm <sup>2</sup>	suitable		
Steel < 1400 N/mm <sup>2</sup>	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Stone	suitable only under restricted conditions		
Paint	suitable		
Uni	suitable		

wet maximum	suitable only under restricted conditions	
dry	suitable	

# **Accessories**

Hand block	556020
Mandrel	556030