

**HOLEX****Fleece finishing belt (A), 20×520 mm, Grit equivalent: 100****Order data**

|              |               |
|--------------|---------------|
| Order number | 558481 100    |
| GTIN         | 4045197719270 |
| Item class   | 52E           |

**Description****Version:**

Synthetic nylon non-woven fabric with synthetic resin bonded abrasive grit, long service life, **consistent surface finish, low heat generation.**

**Application:**

For rubbing down rough ground or brushed surfaces, for consistent and reproducible results. Also suitable for removing rust film, light soiling, and discolouration.

Iron, sulphur and chlorine constituents: < 0.1 %

Grit designation: coarse

Version: A coarse

Colour: brown

**Technical description**

|                  |          |
|------------------|----------|
| Grit equivalent  | 100      |
| Colour           | brown    |
| Grit designation | coarse   |
| Version          | A coarse |

|   |                       |
|---|-----------------------|
| Grinding medium code                    | A                     |
| Iron, sulphur and chlorine constituents | < 0.1 %               |
| Linishing belt width                    | 20 mm                 |
| Linishing belt length                   | 520 mm                |
| Product name attribute                  | 20×520 mm             |
| Type of product                         | Fleece linishing belt |

### User data

|                                | Suitability                               | V <sub>c</sub> | ISO code |
|--------------------------------|---|----------------|----------|
| Alu Mg                         | suitable only under restricted conditions | 15-20 m/s      |          |
| Steel < 900 N/mm <sup>2</sup>  | suitable                                  | 10 m/s         | P        |
| Steel < 1400 N/mm <sup>2</sup> | suitable                                  | 10 m/s         | P        |
| Steel < 55 HRC                 | suitable                                  | 10 m/s         | H        |
| Steel < 60 HRC                 | suitable                                  | 10 m/s         | H        |
| Steel < 67 HRC                 | suitable                                  | 10 m/s         | H        |
| INOX                           | suitable                                  | 10 m/s         |          |
| Ti                             | suitable                                  | 10 m/s         |          |
| GG(G)                          | suitable                                  | 10 m/s         | K        |
| CuZn                           | suitable                                  | 10 m/s         | N        |
| Plastic, GRP                   | suitable                                  | 10 m/s         |          |
| Wood                           | suitable                                  | 10 m/s         |          |
| Paint                          | suitable                                  | 10 m/s         |          |
| Uni                            | suitable                                  | 10 m/s         |          |
| dry                            | suitable                                  |                |          |