

Abrasive flap disc long life CER, conical, Ø 115 mm, Grit: 120



Order data

Order number	565224 120		
GTIN	4062406156091		
Item class	51M		

Description

Version:

- High-quality self-sharpening ceramic grit (CER) for maximum abrasive power and low contact pressure.
- · Active coating for cool cutting.
- Sturdy poly-cotton mixed fabric for ideal wear characteristics and stability, even when used on edges.
- · Ergonomic and vibration-damping polyester plastic backing pad (can be reset).
- · Best results on high-power angle grinders.

long life - very closely spaced flap strips, for maximum tool life.

Application:

General purpose abrasive disc operations, surface abrasion, material removal and edge smoothing.

maximum circumferential speed: 80 m/s

Shape description: dished

Bore Ø: 22.23 mm

Technical description

Shape description	dished		
Grit	120		
Bore Ø	22.23 mm		
Grinding media	Ceramic grit (CER)		
Grinding medium code	Ceramic		
abrasive, cooling coating	yes		
Iron, sulphur and chlorine constituents	< 0.1 %		
Product name attribute	Ø 115 mm		
optimised for material	INOX		
maximum circumferential speed	80 m/s		
Type of product	Abrasive flap disc		

User data

	Suitability	V _c	ISO code
Alu Mg	suitable only under restricted conditions		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable only under restricted conditions		
Uni	suitable		
dry	suitable		

