

Garant

Special flap disc (ZA) with overlap between strips, 115 mm Ø, Grit: 80



Order data

Order number	566290 80
GTIN	4045197720436
Item class	51M

Description

Version:

Flap disc with **extra large overlap between strips (10 mm)**. High metal removal rate and service life due to the use of high-quality **Zirconium Aluminium Oxide (ZA)** on robust mixed fabric. With active coating for cool cutting.

- **Dished shape – for dressing edges/welds and surface grinding with approach angles 15–25°.**

Application:

Ideal for grinding tasks alternating between **surface grinding and contour grinding** and for use in **inaccessible places** such as grinding out of weld fillets.

maximum circumferential speed: 80 m/s

Shape description: dished with overlap between strips

Bore Ø: 22.23 mm

Technical description

Bore Ø	22.23 mm
Shape description	dished with overlap between strips

Grit	80
Disc Ø	115 mm
Grinding medium code	ZA
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	115 mm Ø
optimised for material	Steel
optimised for material	INOX
maximum circumferential speed	80 m/s
Type of product	Abrasive flap disc

User data

	Suitability	V _c	ISO code
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable only under restricted conditions		
GG(G)	suitable		
Uni	suitable only under restricted conditions		
dry	suitable		