

Flap disc Fleece/fabric, Ø 125 mm, Grit equivalent: 80MED



Order data

Order number	566335 80MED		
GTIN	4045197890399		
Item class	51M		

Description

Version:

Flap disc with a combination of cloth flaps of **abrasive cloth (A)** in 80 grit and **fleece (medium). High metal removal rate** and consistent **surface finish** in a single pass. **Application:**

TIG weld seam smoothing, surface and contour grinding, deburring work. Recommended speed 6500 rpm.

maximum circumferential speed: 80 m/s

recommended speed: 6500 min⁻¹

Shape description: dished

Bore Ø: 22.23 mm

Technical description

Disc Ø	125 mm		
Bore Ø	22.23 mm		
Shape description	dished		
Grit equivalent	80		
Grinding medium code	Α		



Iron, sulphur and chlorine constituents	< 0.1 %	
Product name attribute	Ø 125 mm	
optimised for material	INOX	
maximum circumferential speed	80 m/s	
recommended speed	6500 min ⁻¹	
Type of product	Abrasive flap disc	

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
Plastic, GRP	suitable		
Paint	suitable		
Uni	suitable		
dry	suitable		