



Flap wheel roller M14 Fleece/fabric, Ø 100 × 50 mm, Grit equivalent: 80CRS



Order data

| | |
|--------------|---------------|
| Order number | 566372 80CRS |
| GTIN | 4045197924605 |
| Item class | 52M |

Description

Version:

Strips arranged in a fan form around the axis of the tool. **M14 direct mounting.**

Combination of **abrasive cloth and fleece.**

Application:

Removes scratches, gives a brushed matt effect.

maximum circumferential speed: 30 m/s

recommended speed: 2800 min⁻¹

maximum speed: 6000 min⁻¹

Technical description

| | |
|---|------------------------|
| recommended speed | 2800 min ⁻¹ |
| Grit equivalent | 80 |
| maximum speed | 6000 min ⁻¹ |
| Grinding medium code | A |
| Iron, sulphur and chlorine constituents | < 0.1 % |

| | |
|-------------------------------|--------------------------------|
| Thread | M14 |
| Roller Ø | 100 mm |
| Roller width | 50 mm |
| Product name attribute | Ø 100 × 50 mm |
| optimised for material | Steel |
| optimised for material | INOX |
| maximum circumferential speed | 30 m/s |
| Type of product | Flap wheel roller fabric, slit |

User data

| | Suitability | V _c | ISO code |
|--------------------------------|---|----------------|----------|
| Alu Mg | suitable | | |
| Steel < 900 N/mm ² | suitable | | |
| Steel < 1400 N/mm ² | suitable | | |
| Steel < 55 HRC | suitable | | |
| Steel < 60 HRC | suitable | | |
| Carbide (HM) | suitable only under restricted conditions | | |
| INOX | suitable | | |
| Ti | suitable | | |
| GG(G) | suitable | | |
| CuZn | suitable | | |
| Plastic, GRP | suitable | | |
| Wood | suitable only under restricted conditions | | |
| Paint | suitable | | |
| Uni | suitable | | |
| dry | suitable | | |

