

### Coarse cleaning disc (SiC), Disc Ø: 115mm



### Order data

Order number	566750 115
GTIN	4045197566102
Item class	52E

## **Description**

#### **Version:**

Cleaning discs with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad.

Very **coarse non-woven abrasive mesh structure**, will not clog even when used on soft thick coatings.

Hard and aggressive fleece body for **general-purpose use** on large areas.

### **Application:**

For rust removal, paint removal, dressing weld seams and removing surface dirt.

With glass fibre backing pad for direct clamping on angle grinders.

#### Note:

For deburring wheels for double-ended bench grinding machines, see No. 556270 onwards. maximum circumferential speed: 60 m/s

Grit designation: very coarse

Bore Ø: 22.23 mm Bore Ø: 22.23 mm

recommended speed: 5000 - 7000 min<sup>-1</sup>

maximum speed: 11000 min<sup>-1</sup>

## **Technical description**



recommended speed	5000 - 7000 min <sup>-1</sup>	
Bore Ø	22.23 mm	
maximum speed	11000 min <sup>-1</sup>	
Disc Ø	115 mm	
Grinding medium code	SiC	
Degree of hardness	hard	
Grit designation	very coarse	
Iron, sulphur and chlorine constituents	< 0.1 %	
Shape description	flat	
maximum circumferential speed	60 m/s	
Type of product	Rough cleaning non- woven abrasive mesh	

# **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Alu Mg	suitable		
Steel < 900 N/mm <sup>2</sup>	suitable		
Steel < 1400 N/mm <sup>2</sup>	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Paint	suitable		
Uni	suitable		

wet maximum	suitable only under restricted conditions	
dry	suitable	