


Garant

Abrasive flap wheel roller, fabric (CER), Ø 100 × 100 mm, Grit: 60



Order data

| | |
|--------------|---------------|
| Order number | 568463 60 |
| GTIN | 4062406287078 |
| Item class | 51M |

Description

Version:

Flap strips of abrasive cloth around the shank of the flap brush. Standard size **Ø 100×100 mm** or narrow version **Ø 100×50 mm** for grinding smaller areas. Mounting bore Ø 19 mm with multiple splines.

Application:

Ceramic grit (CER) ideal for working on stainless steels and nickel alloys. High removal rate and cool cut.

Note:

For matching the width of narrow rollers Ø 100×50 mm use the spacer ring pack No. 568439.

Iron, sulphur and chlorine constituents: < 0.1 %

Grinding media backing: Fabric

recommended speed: 3700 min⁻¹

Technical description

| | |
|------------------------|------------------------|
| Grinding media backing | Fabric |
| Grit | 60 |
| recommended speed | 3700 min ⁻¹ |
| Grinding media | Ceramic grit (CER) |

| | |
|---|--------------------------------|
| Grinding medium code | Ceramic |
| Iron, sulphur and chlorine constituents | < 0.1 % |
| Roller Ø | 100 mm |
| Roller width | 100 mm |
| Product name attribute | Ø 100 × 100 mm |
| Bore Ø | 19 mm |
| Type of product | Flap wheel roller fabric, slit |

User data

| | Suitability | V _c | ISO code |
|--------------------------------|---|----------------|----------|
| Alu Mg | suitable only under restricted conditions | | |
| Steel < 900 N/mm ² | suitable | | |
| Steel < 1400 N/mm ² | suitable | | |
| Steel < 55 HRC | suitable | | |
| Steel < 60 HRC | suitable | | |
| Steel < 67 HRC | suitable | | |
| INOX | suitable | | |
| Ti | suitable | | |
| GG(G) | suitable only under restricted conditions | | |
| CuZn | suitable only under restricted conditions | | |
| dry | suitable | | |