

# Abrasive flap wheel roller, fleece (ZA), $\varnothing$ 100 $\times$ 100 mm, Grit equivalent: 280



### **Order data**

Order number	568477 280		
GTIN	4062406288310		
Item class	51M		

### **Description**

#### **Version:**

Standard size  $\emptyset$  **100**×**100 mm** or narrow version  $\emptyset$  **100**×**50 mm** for grinding smaller areas. Mounting bore  $\emptyset$  19 mm with multiple splines.

Especially wear-resistant and fine-structured fleece with Zirconium Aluminium Oxide (ZA). Ideal for use on stainless steel.

#### **Application:**

Fine fleece for light cleaning work and a uniform surface finish.

#### Note

For matching the width of narrow rollers  $\varnothing$  100×50 mm use the spacer ring pack No. 568439.

Bore Ø: 19 mm

Grinding media backing: Cleaning non-woven abrasive mesh

recommended speed: 2800 min<sup>-1</sup>

## **Technical description**

Grinding media backing	Cleaning non-woven abrasive mesh		
Grit equivalent	280		
recommended speed	2800 min <sup>-1</sup>		
Grinding media	Zirconium abrasive (ZA)		

Grinding medium code	ZA		
Iron, sulphur and chlorine constituents	< 0.1 %		
Roller Ø	100 mm		
Roller width	100 mm		
Product name attribute	Ø 100 × 100 mm		
Bore Ø	19 mm		
Type of product	Abrasive flap wheel roller, fleece		

# **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Alu Mg	suitable		
Steel < 900 N/mm <sup>2</sup>	suitable		
Steel < 1400 N/mm <sup>2</sup>	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable only under restricted conditions		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Paint	suitable only under restricted conditions		
dry	suitable		